

# SmartLogger1000



## Smart

- Modbus-TCP for connections to Huawei NetEco
- IEC60870-5-104 for connections to third-party monitoring systems
- USB and embedded web for data reading and software upgrade
- Automatically detecting facilities and mapping RS485 addresses
- Remote control of active & reactive power
- I-V Curve Diagnosis supported

## Simple

- Up to 80 inverters per SmartLogger1000
- Up to 30 devices per RS485 bus
- Easy to install on walls, tabletops and rails

## Reliable

- Max. reliable communication range of 1,000m

Technical Specifications	SmartLogger1000
	<b>Device Management</b>
Max. Number of Manageable Devices	80
Max. Number of Manageable Smart Inverters	80
	<b>Communication Interface</b>
Electrical Ethernet	ETH x 1, 10 / 100 Mbps
RS485	COM x 3, 2400 / 4800 / 9600 / 19200 / 115200 bps
Digital / Analog Input / Output	DI x 4, DO x 3, AI x 2
	<b>Communication Protocol</b>
Ethernet	Modbus-TCP, IEC 60870-5-104
RS485	Modbus-RTU, IEC 60870-5-103 (standard), DL / T645
	<b>Interaction</b>
LCD	3.5 inches Graphic LCD
LED	LED Indicator x 3
WEB	Embedded WEB
USB	USB2.0 x 1
	<b>Environment</b>
Operating Temperature	-20 °C ~ 60 °C (-4 °F ~ 140 °F)
Relative Humidity	5% ~ 95%
Max. Operating Altitude (Non-condensing)	4,000 m (13,123 ft.)
	<b>Mechanical</b>
Power Supply	100 Vac ~ 240 Vac, 50 Hz / 60 Hz
Power Consumption	Typical 3 W, Max. 7 W
Dimensions (W x H x D)	225 x 140 x 50 mm (8.9 x 5.5 x 2.0 inches)
Weight	0.5 kg (1.1 lb.)
Protection Rating	IP20
Installation Option	Wall Mounting, Rail Mounting, Tabletop Mounting